



MAIN FEATURES

- Cassette technology, placed on top of the cooler
- High-quality LED light (canopy & two (2) inner lighting)
- Large and smooth surfaces for branding
- Optimized footprint, still maximum internal volume
- Low energy consumption
- Easy to maintain & move
- Leveling feet could be adjusted from inside the cooler
- Environment friendly refrigerant R290
- Electronic controller
- Door opening: reversible



TECHNICAL DETAILS

	CELIT MDC 60 PRO
Net weight (kg)	89,5
Gross volume (l)	491
Net volume (l)	415
External dimensions W x D x H (mm)	595 x 695 x 2015
Internal dimensions W x D x H (mm)	520 x 535 x 1645
Power input W (220-240V, 50Hz)	210
Defrosting	Automatic
Lighting	2 x vertical LED
Compressor	Danfoss
Refrigerant	R600a
Evaporator type	Finned coil
Condenser type	Steel / Maintenance free
Temperature control	Electronical

TEMPERATURES

Temperature range	+0°C to +6°C
Operating conditions min - max	+10°C to +30°C/55%RH
Classification EN 23953	4H2*

ENERGY CONSUMPTION

	EN 23953
Energy consumption (kWh/24h)	4,8
Without door opening test (kWh/24h)	3,2
Energy class	C

SHELF DIMENSIONS

Adjustable shelf W x D (mm)	484 x 505
Amount of adjustable shelves (pcs)	5
Bottom layer W x D (mm)	505 x 535

TRANSPORTATION

Gross weight (kg)	96
Package size W x D x H (mm)	640 x 750 x 2100
Quantity in 20ft container (pcs)	27
Quantity in 40ft container (pcs)	54
Quantity in 13,6m truck (pcs)	60

OPTIONS

- Full branding
- Special color (RAL color system)
- Extra shelf / product dividers on shelves

W x D x H W 595 mm D 695 mm H 2050 mm	HC R600a	0.25 L 900 pcs	0.5 L 294 pcs	13.6 M 60 pcs	W x D x H W 640 mm D 750 mm H 2100 mm
KG 89,5 kg	RANGE +0°C to +6°C	0.33 L 588 pcs	0.33L 400 pcs	40ft 54 pcs	KG 96 kg

*You can check the detailed information from the beginning of the product catalogue or via the link: www.astecoolers.com/products