



### MAIN FEATURES

- Cassette technology, placed on top of the cooler
- Large and smooth surfaces for branding
- Optimized footprint, still maximum internal volume
- Low energy consumption
- Five (5) adjustable shelves
- Easy maintenance
- Easy to move with high-quality wheels
- Environment-friendly refrigerant R600a
- Door lock
- Door opening: reversible



### TECHNICAL DETAILS

	Celit MDC40
Net weight (kg)	95
Gross volume (l)	256
Net volume (l)	
External dimensions W x D x H (mm)	400 x 595 x 2000
Internal dimensions W x D x H (mm)	310 x 505 x 1640
Power input W (220-240V, 50Hz)	180
Defrosting	Automatic
Compressor	Danfoss
Refrigerant	R600a
Energy consumption (kWh/24h)	2,6
Evaporator type	Finned coil
Condenser type	Maintenance free
Temperature control	Electronical
Noise level (db)	46
Length of connection cable (m)	3
Door opening	Reversible

### TEMPERATURES

Temperature range	+3°C to +8°C
Operating conditions min - max	+10°C to +25°C/60%RH

### SHELF DIMENSIONS

Adjustable shelf 1 W x D (mm)	300 x 455
Amount of adjustable shelves (pcs)	5
Bottom layer W x D (mm)	310 x 482

### TRANSPORTATION

Gross weight (kg)	105
Package size W x D x H (mm)	450 x 650 x 2150
Quantity in 20ft container (pcs)	39
Quantity in 40ft container (pcs)	78
Quantity in 13,6m truck (pcs)	90

### OPTIONS

Full branding	
Special color (RAL color system)	
Stainless steel housing	
Product dividers on shelves	
Extra shelf	
Energy Management Controller (EMC)	
Smart Monitoring Interface (SMI)	

W x D x H W 400mm D 595mm H 2000mm	HC R600a	0.25 L 528 pcs	0.5 L 168 pcs	13.6 M 90 pcs	W x D x H W 450 mm D 650 mm H 2150 mm
KG 95 kg	RANGE +3°C to +8°C	0.33 L 336 pcs	0.33L 215 pcs	40ft 78 pcs	KG 105 kg